

EUROLITE CLEAR (VARNISH)

➤ Scope

Any varnish or clear have the least resistance to UV rays of the sun. Therefore, we do not recommend any clear for outdoor application. However, for indoor, Eurolite Clear will offer a very long lasting gloss.

Another important feature of Eurolite Clear, is its capability to enhance gloss of any synthetic enamel but should not be used more than twenty five percent of the enamel, volume to volume.

➤ Areas of Application

Metal and wood.

➤ Surface Preparation

Please refer to our pamphlets on:

“Surface preparation of metals”

“Surface preparation of wood”

➤ Technical Data

- APPEARANCE : Light yellow, clear liquid.
- VISCOSITY : 95 ± 5 sec. By f.c. No.4 @30°c.
- WEIGHT/LITRE : 0.90 ± 0.02 kg./ltr.
- DRYING TIME : Touch dry : 1 to 1½ hrs.
Surface dry : 4½ to 5 hrs.
Hard dry : 24 hrs.
- FLEXIBILITY : Passes 1/4” bending mandrel.
- SCRATCH HARDNESS : 1000 gms. After 48 hours.
- CROSS HATCH TEST : Passes
- FINISH : Smooth and glossy.

➤ Directions for Use

Prepare the surface as directed above. Start applying to wood or to metal for interior use. Mix maximum up to 25% volume to volume, in any synthetic enamel, for enhancing the gloss.

➤ Disclaimer

The information contained within this data sheet is based on information believed to be reliable at the time of its preparation. The company will not be liable for loss or damage howsoever caused including liability for negligence, which may be suffered by the user of the data contained herein. It is the users’ responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of results is implied since conditions of use are beyond our control.