

## ROSALEE NO RUST PM RED, BLUE AND BLACK FAST DRYING TEMPORARY RUST PREVENTING VARNISH

### ➤ **Composition**

This is phenolic modified fast drying varnish for industrial application.

### ➤ **Recommended Applications**

This product is recommended to use as temporary rust preventive coating and can be applied on prefabricated m.s. Sheets, angles, sections and castings etc. This varnish can be applied by brushing, spraying or dipping depending upon the shape and size of the article. Two or three liberal coats are enough to prevent it from rusting. This product is not weld able and needs to be removed before welding. Varnish in a sound condition can directly be over coated with primers and top coats or otherwise must be removed by sanding or eurostrip paint removed before painting.

### ➤ **Technical Data**

|               |   |                                   |
|---------------|---|-----------------------------------|
| COLOUR        | : | Red, blue and black (transparent) |
| FINISH        | : | Glossy                            |
| VISCOSITY     | : | 20 ± 2 sec.                       |
| VOLUME SOLIDS | : | 33 ± 2%                           |
| DRYING TIME   | : | Surface dry : 20 to 30 minutes.   |
|               |   | Hard dry : 6 to 8 hours.          |

### ➤ **Typical Application Systems And Equipments**

The surface must be clean and dry, free from oils, dirt and moisture before application. This product is generally applied by brush, dipping and conventional spray application

#### **Brush application:**

|          |   |                      |
|----------|---|----------------------|
| Thinner  | : | quick drying thinner |
| Addition | : | 5 %, if required     |

#### **Conventional spray application setting:**

|                 |   |                      |
|-----------------|---|----------------------|
| Thinner         | : | quick drying thinner |
| Addition        | : | 5 %, if required     |
| Nozzle orifice  | : | 1.2 -1.4 mm          |
| nozzle pressure | : | 40-50 psi            |

### ➤ **Surface Preparation**

The surface must be clean and dry, free from oils, dirt and moisture before application.

## ROSALEE NO RUST PM RED, BLUE AND BLACK FAST DRYING TEMPORARY RUST PREVENTING VARNISH

### ➤ **Health And Safety**

This varnish contains organic solvents and pigments. Mixing and handling of this product this paints must be carried out with taking proper safety measures to avoid skin contacts, eye contacts, and inhalation of solvent vapours and mist of the paint spray. The painting must be carried out in a well ventilated spray booths fitted with proper exhaust systems. If painting is to be done on site, care must be taken that along with the spray painter; other people in the nearby area are also protected in the same manner as the painter.

### ➤ **Disclaimer**

The information contained within this data sheet is based on information believed to be reliable at the time of its preparation. The company will not be liable for any loss or damage whatsoever occurred including liability for negligence, which may be suffered by the user of the data contained herein. It is the users' responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of results is implied since conditions of use are beyond our control.