

TRENDZ INTERIOR EMULSION PAINT PURE ACRYLIC EMULSION BASED PAINT FOR INTERIORS

➤ Scope

Interior emulsion paint is pure Acrylic emulsion based paint meant for high quality matt finish for interiors.

➤ Areas of Application

This product is recommended to be applied on interior wall plaster and masonries. This is 1st quality paint with high coverage and opacity. It resists atmospheric humidity and moderate washings. This product should not be used in areas where frequent contacts with water or water vapours are possible. This paint also fungus and mildew resistant.

➤ Technical Data

- Colour : White and pastels to dark
- Finish : Smooth and matt
- NVM of the product : 55 ± 3%, may vary according to colours.

- Theoretical spreading rate : 12 to 14 sq.mt / ltr
- Drying characteristics : Surface Dry : 30 to 40 minutes
(At 30^oc & 65% relative humidity) Dry to Overcoat: 4-6hours

- Application : By brush, roller and spray

- Thinner : Water; add up to 50 to 60% as required
- Self life : 12 Months in originally sealed containers.

➤ Directions for Use

It is recommended to apply water based wall primer first and then apply 2 to 3 coats of putty at an interval of 4 to 6 hours. Special care is required while filling the cracks and joints of the wall to ensure smooth and continuous look. Sand the putty with sand paper and apply one coat of water based wall primer before applying the Interior emulsion paint. Apply 2 to 3 coats of Interior emulsion paint to finish the job.

➤ Note

Do not apply thick coats of putty all at once. This may lead to cracks and peeling off the paint systems.

TRENDZ INTERIOR EMULSION PAINT PURE ACRYLIC EMULSION BASED PAINT FOR INTERIORS

➤ **Surface Preparation**

Wall putty can be applied on plasters and masonries. They must be dry and matured at least for 3 months. At the time application dust prevention is must to achieve good results. This product is for interior use only.

➤ **Health and safety**

Wall putty contains water based binder, extenders and white pigments. Mixing and handling of this product this paints must be carried out with taking proper safety measures to avoid skin contacts, eye contacts, and inhalation of solvent vapours.

➤ **Disclaimer**

The information contained within this data sheet is based on information believed to be reliable at the time of its preparation. The company will not be liable for any loss or damage whatsoever occurred including liability for negligence, which may be suffered by the user of the data contained herein. It is the users' responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of results is implied since conditions of use are beyond our control.